

1-800-375-0605 www.rudolphbros.com

Authorized Distributor

Printing date 01/30/2019 Revision 3 Reviewed on 01/30/2019

1 Identification

· Product identifier

· Trade name: <u>UB-50 (Isocyanate, PART-A)</u> · Product number: UB-50 (Isocyanate, Part-A)

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

EPOXYSET INC. 718 Park East Drive

Woonsocket, RI 02895, USA Phone: (401) 726-4500

Phone: (401) 726-4500 www.epoxyset.com

· Information department: Product safety department: msds@epoxyset.com

· Emergency telephone number:

Chemtel (US transportation) 1-800-255-3924 International (call collect) +01-813-248-0585

2 Hazard(s) identification

· Classification of the substance or mixture



GHS08 Health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Carc. 2 H351 Suspected of causing cancer.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335 May cause respiratory irritation.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



· Signal word Danger

(Contd. on page 2)

Printing date 01/30/2019 Revision 3 Reviewed on 01/30/2019

Trade name: UB-50 (Isocyanate, PART-A)

(Contd. of page 1)

· Hazard-determining components of labeling:

4,4'-methylenediphenyl diisocyanate

Diphenylmethane Diisocyanate (MDI) Mixed Isomers

· Hazard statements

H332 Harmful if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing must not be allowed out of the workplace.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

P284 [In case of inadequate ventilation] wear respiratory protection.

P302+P352 If on skin: Wash with plenty of water.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P312 Call a poison center/doctor if you feel unwell.

P321 Specific treatment (see on this label).

P314 Get medical advice/attention if you feel unwell.

P362+P364 Take off contaminated clothing and wash it before reuse.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.

P342+P311 If experiencing respiratory symptoms: Call a poison center/doctor.

P363 Wash contaminated clothing before reuse.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Classification system:

· NFPA ratings (scale 0 - 4)



Health = 2Fire = 1Reactivity = 0

· HMIS-ratings (scale 0 - 4)



- Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.

(Contd. on page 3)

Printing date 01/30/2019 Revision 3 Reviewed on 01/30/2019

Trade name: UB-50 (Isocyanate, PART-A)

· **vPvB**: Not applicable.

(Contd. of page 2)

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- **Description:** Mixture of the substances listed below with nonhazardous additions.

· Dangerous	components:		
101-68-8	4,4'-methylenediphenyl diisocyanate	>50%	
26447-40-5	Diphenylmethane Diisocyanate (MDI) Mixed Isomers	<30%	

4 First-aid measures

- · Description of first aid measures
- · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Not required.
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

(Contd. on page 4)

Printing date 01/30/2019 Revision 3 Reviewed on 01/30/2019

Trade name: UB-50 (Isocyanate, PART-A)

· Protective A	Action Criteria for Chemicals	(Contd. of page 3)
· PAC-1:		
101-68-8	4,4'-methylenediphenyl diisocyanate	0.45 mg/m^3
26447-40-5	Diphenylmethane Diisocyanate (MDI) Mixed Isomers	29 mg/m³
· PAC-2:		
101-68-8	4,4'-methylenediphenyl diisocyanate	5 mg/m³
26447-40-5	Diphenylmethane Diisocyanate (MDI) Mixed Isomers	40 mg/m ³
· PAC-3:		
101-68-8	4,4'-methylenediphenyl diisocyanate	55 mg/m ³
26447-40-5	Diphenylmethane Diisocyanate (MDI) Mixed Isomers	240 mg/m ³

7 Handling and storage

- · Handling:
- · Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a closed container.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit

At this time, the remaining constituent has no known exposure limits.

	101-68-8 4,4'-methylenediphenyl diisocyanate		
PEL	Ceiling limit value: 0.2 mg/m³, 0.02 ppm		
	Long-term value: 0.05 mg/m³, 0.005 ppm Ceiling limit value: 0.2* mg/m³, 0.02* ppm *10-min		
TLV	Long-term value: 0.051 mg/m³, 0.005 ppm		

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

(Contd. on page 5)

Printing date 01/30/2019 Revision 3 Reviewed on 01/30/2019

Trade name: UB-50 (Isocyanate, PART-A)

(Contd. of page 4)

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties				
· Information on basic physical and chemical properties · General Information · Appearance:				
Form:	Liquid			
Color:	Light yellow			
· Odor:	Characteristic			
· Odor threshold:	Not determined.			
· pH-value:	Not determined.			
· Change in condition Melting point/Melting range: Boiling point/Boiling range:	Undetermined. 208 °C (406.4 °F)			
· Flash point:	200 °C (392 °F)			
· Flammability (solid, gaseous):	Not applicable.			
· Ignition temperature:	520 °C (968 °F)			
· Decomposition temperature:	Not determined.			
· Auto igniting:	Product is not selfigniting.			
· Danger of explosion:	Product does not present an explosion hazard.			
· Explosion limits: Lower: Upper:	0.4 Vol % 0.0 Vol %			
· Vapor pressure:	Not determined.			
· Density at 20 °C (68 °F):	1.22 g/cm³ (10.1809 lbs/gal)			

(Contd. on page 6)

Printing date 01/30/2019 Revision 3 Reviewed on 01/30/2019

Trade name: UB-50 (Isocyanate, PART-A)

(Contd. of page 5)

Relative density
 Vapor density
 Evaporation rate
 Not determined.
 Not determined.

· Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic: Not determined. Kinematic: Not determined.

· Solvent content:

VOC content: 0.00 %

0.0 g/l / 0.00 lb/gal

• Other information No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

101-68-8 4,4'-methylenediphenyl diisocyanate

Oral LD50 2,200 mg/kg (mouse)

- · Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- · on the eve: Irritating effect.
- · Sensitization:

Sensitization possible through inhalation.

Sensitization possible through skin contact.

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

101-68-8 4,4'-methylenediphenyl diisocyanate

3

· NTP (National Toxicology Program)

None of the ingredients is listed.

(Contd. on page 7)

Printing date 01/30/2019 Revision 3 Reviewed on 01/30/2019

Trade name: UB-50 (Isocyanate, PART-A)

(Contd. of page 6)

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

4 Transport information		
· UN-Number · DOT, ADN, IMDG, IATA	not regulated	
· UN proper shipping name · DOT, ADN, IMDG, IATA	not regulated	
Transport hazard class(es)		
· DOT, ADN, IMDG, IATA · Class	not regulated	
Packing group DOT, IMDG, IATA	not regulated	
Environmental hazards: Marine pollutant:	No	
Special precautions for user	Not applicable.	
Transport in bulk according to Annex I MARPOL73/78 and the IBC Code	II of Not applicable.	

(Contd. on page 8)

Printing date 01/30/2019 Revision 3 Reviewed on 01/30/2019

Trade name: UB-50 (Isocyanate, PART-A)

(Contd. of page 7)

· UN "Model Regulation": not regulated

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- ·Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

101-68-8 4,4'-methylenediphenyl diisocyanate

TSCA (Toxic Substances Control Act):

All ingredients are listed.

- · Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

- · Carcinogenic categories
- · EPA (Environmental Protection Agency)

101-68-8 4,4'-methylenediphenyl diisocyanate

D, CBD

· TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS07 GHS08

- · Signal word Danger
- · Hazard-determining components of labeling:

4,4'-methylenediphenyl diisocyanate

Diphenylmethane Diisocyanate (MDI) Mixed Isomers

- · Hazard statements
- H332 Harmful if inhaled.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

(Contd. on page 9)

Printing date 01/30/2019 Revision 3 Reviewed on 01/30/2019

Trade name: UB-50 (Isocyanate, PART-A)

(Contd. of page 8)

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

H335 May cause respiratory irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling. P264

Use only outdoors or in a well-ventilated area. P271

Contaminated work clothing must not be allowed out of the workplace. P272 P280 Wear protective gloves/protective clothing/eye protection/face protection.

P284 [In case of inadequate ventilation] wear respiratory protection.

P302+P352 If on skin: Wash with plenty of water.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention. P308+P313

P312 Call a poison center/doctor if you feel unwell.

P321 Specific treatment (see on this label).

P314 Get medical advice/attention if you feel unwell.

Take off contaminated clothing and wash it before reuse. P362+P364 If skin irritation or rash occurs: Get medical advice/attention. P333+P313 If eye irritation persists: Get medical advice/attention. P337+P313

P342+P311 If experiencing respiratory symptoms: Call a poison center/doctor.

Wash contaminated clothing before reuse. P363

Store in a well-ventilated place. Keep container tightly closed. P403+P233

P405 Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations. P501

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact: Mr. Patel
- · Date of preparation / last revision 01/30/2019 / 2
- · Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value PEL: Permissible Exposure Limit

(Contd. on page 10)

Printing date 01/30/2019 Revision 3 Reviewed on 01/30/2019

Trade name: UB-50 (Isocyanate, PART-A)

(Contd. of page 9)

REL: Recommended Exposure Limit Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A

Resp. Sens. 1: Respiratory sensitisation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

Carc. 2: Carcinogenicity - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

* * Data compared to the previous version altered.

TIC

Authorized Distributor

